

Au cœur d’une pipeline: démystifions Vite et ses plugins


VITE


- Webpack
- Vite
- Rspack
- Snowpack
- SWC




compiler → executable
bundler → bundle



Type your message...


Web Server
Based on ECMAScript Modules
Transform Files On-Demand
Extensible using Plugins

HTTP Logs

```
GET http://localhost:5173/
GET http://localhost:5173/src/main.ts?t=1772882882631
GET http://localhost:5173/src/style.css?t=1772882882631
GET http://localhost:5173/node_modules/.vite/deps/vue.js?v=ed2c93c8
GET http://localhost:5173/src/App.vue
```

HTML

Use HTML as an entry point with automatic script and asset handling.

JSX

Use JSX with built-in transformation and framework support.

CSS

Import CSS with support for HMR, modules, and preprocessors.

Static Assets

Import static assets such as images, fonts, and media.

JSON

Import JSON files directly as JavaScript modules.

Glob Import

Import multiple modules using a file pattern.

Dynamic Import

Load modules dynamically with native code splitting.

WebAssembly

Import and run WebAssembly modules from JavaScript.

Web Workers

Run code in background threads using Web Workers.

Feature Plugins = Everything is a Plugin

CSS Imported into a TypeScript File

3 / 9 · 33%

3

VOTES

An Image Loaded in a TypeScript File

4 / 9 · 44%

4

VOTES

JSX Loaded Naturally


2 / 9 · 22%

2

VOTES





```
import './style.css'
```


Elements
Console
Sources
Network
Performance
Memory
Application
Security
All
Fetch/XHR
Doc
CSS
JS
Font
Img
Media
Manifest
Socket
Wasm
Other
Name
Method
Status
Protocol
Type
Initiator
Size
Time
Waterfall
1 localhost GET 200 http/1.1 document Other - 6 ms
2 main.ts GET 200 http/1.1 script (index):13 - 26 ms
3 style.css GET 200 http/1.1 stylesheet main.ts:1 - 4 ms

```
import img from './image.png'
```






Feature Plugins – An Image Loaded in a TypeScript File – Visualization


Vite Build Output
dist
index.html
assets
image-DNpSpoYj.jpg
JS
index-CgILWvq0.js

```
1   import { createRoot } fr
2   import { Item } from './I
3
4   function App() {
5     return (
6       <div>
7         <h1>My App</h1>
8         <Item name="Item 1"
9         <Item name="Item 2"
10      </div>
11    )
12  }
13
14  const root = createRoot(
15  root.render(<App />)
```




Elements
Console
Sources
Network
Performance
Memory
Application
Security
All
Fetch/XHR
Doc
CSS
JS
Font
Img
Media
Manifest
Socket
Wasm
Other
Name
Method
Status
Protocol
Type
Initiator
Size
Time
Waterfall
1 localhost GET 200 http/1.1 document Other - 6 ms
2 JS main.jsx GET 200 http/1.1 script (index):13 - 26 ms
3 JS item.jsx GET 200 http/1.1 script main.jsx:1 - 4 ms
Feature Plugins – JSX Loaded Naturally – Visualization

Vite in 3 Points



1

A web server for development

It handles requests that can be transformed on demand

2


A bundler for production

It transforms our code for production

3

A plugin system

To extend its features and make it do whatever we want


export default function myPlugin() {
return {
name: 'my-plugin',
resolveId() {},
load() {},
transform() {},
}
}


export function myPlugin() {
return {
name: 'my-plugin',
resolveId(id) { // /src/components/HelloWorld.vue
if (id.endsWith('.vue')) {
return id
}
},
}
}


export function myPlugin() {
return {
name: 'my-plugin',
async load() {
return "export default 'Hello World'"
}
},
}


export function myPlugin() {
return {
name: 'my-plugin',
transform(code, id) {
if (id.endsWith('.vue')) {
return transformSFC(code, filename)
}
}
},
}

Multiple plugins?

request

resolveId `resolveId (id)`

VuePlugin

CustomPlugin

load `load (id)`

VuePlugin

CustomPlugin

transform `transform (code, id)`

VuePlugin

CustomPlugin

response

input

output

vite-plugin-inspect

```
export default function myPlugin() {
  let config = null
  return {
    name: 'my-plugin',
    config(config) {
      config.root = 'src'
    },
    configResolved(resolvedConfig) {
      config = resolvedConfig
    },
    async buildStart() {
      await scanDir(config.root)
    },
    async buildEnd() {
      await generateSitemap(config)
    },
  }
}
```


So what does
that look like?

Simple Transform Plugin

HTTP Logs

```
GET http://localhost:5173/
GET http://localhost:5173/src/main.ts?t=1773357600000
```



```
export default function simpleTransform() {
  return {
    name: "simple-transform",
    transform(code) {
      return code.replace("__BUILD_TIME__", new Date().toString())
    }
  }
}
```

External Markdown Loader

HTTP Logs

```
GET http://localhost:5173/
GET http://localhost:5173/src/main.ts?t=1773357600000
GET http://localhost:5173/src/daily-news.md?t=1773357600001
```

```ts
import markdownit from 'markdown-it'

export default function externalMarkdown() {
  const md = markdownit()

  return {
    name: "external-markdown",
    async load(id) { // /src/daily-news.md
      if (!id.endsWidth(".md"))
        return

      return fetch(`https://api.example.com/${id}`).then(res => res.text())
    },
    async transform(code, id) {
      if (!id.endsWidth(".md"))
        return

      return `const html = "${md.render(code)}"\n\nexport default html`
    }
  }
}
```

The Vite Plugin in 3 Points



1. **A Vite plugin is a function that returns an object**
   That object must at least have a name property

2. **There are 3 main hooks to act on modules**
   resolveId, load, and transform

3. **There are also hooks for Vite's lifecycle**
   config, configResolved, buildStart, buildEnd, and closeBundle





```
export default function myPlugin() {
  return {
    name: 'my-plugin',
    resolveId(id) {
      // Used to intercept the module identifier and return a new one
    },
    load(id) {
      // Used to return the content of a module given its identifier
    },
    transform(code, id) {
      // Used to transform the content of a module given its identifier
    }
  }
}
```

A Plugin for Virtualization

HTTP Logs

```
GET http://localhost:5173/
GET http://localhost:5173/src/main.ts?t=1772882882631
GET http://localhost:5173/@id/__x00__virtual:my-module
```



```
export default function myVirtualModulePlugin() {
  const virtualModuleId = 'virtual:my-module'
  const resolvedVirtualModuleId = '\0' + virtualModuleId

  return {
    name: 'my-virtual-module-plugin',
    resolveId(id) {
      if (id === virtualModuleId) {
        return resolvedVirtualModuleId
      }
    },
    load(id) {
      if (id === resolvedVirtualModuleId) {
        return `export const msg = "from virtual module"`
      }
    },
  }
}
```

```
import { defineConfig } from 'vite'
import virtual from 'vite-plugin-virtual'

export default defineConfig({
  plugins: [
    virtual({
      'virtual:git:commit': () => {
        const commit = execSync('git rev-parse HEAD').toString().trim()
        return `export default "${commit}"`
      },
      'virtual:api:data': async () => {
        const res = await fetch('https://api.example.com/data')
        const data = await res.json()
        return `export default ${JSON.stringify(data)}`
      },
    })
  ]
})
```

Vue Router - A Virtual Module

0 / 10 · 0%

0

VOTES

VitePress - Virtual Data

4 / 10 · 40%

4

VOTES

Icons Plugin - Virtual Icons

6 / 10 · 60%

6

VOTES

Info Plugin - Virtual Information

0 / 10 · 0%

0

VOTES


import { createApp } from 'vue'
import { createRouter, createWebHistory } from 'vue-router'
import { routes } from 'vue-router/auto-routes'
import App from './App.vue'
const router = createRouter({
history: createWebHistory(),
routes,
})
createApp(App)
.use(router)
.mount('#app')

```ts
import fs from 'node:fs/promises'

export default function autoRoutes() {
  return {
    name: 'auto-routes',
    resolveId(id) {
      if (id === 'vue-router/auto-routes') {
        return '\0vue-router/auto-routes'
      }
    },
    load(id) {
      if (id === '\0vue-router/auto-routes') {
        const files = await fs.readdir('./src/pages')
        const routes = await generateRoutes(files)
        return `export const routes = ${JSON.stringify(routes)}`
      }
    },
  }
}
```

```js
// example.data.js
export default {
  load() {
    return {
      hello: 'world'
    }
  }
}
```

```vue
<!-- example.vue -->
<script setup>
import { data } from './example.data.js'
</script>

<pre>
{{ data.hello }} <!-- "world" -->
</pre>
```

```ts
import { defineConfig } from 'vite'

export default defineConfig({
  plugins: [
    {
      name: 'data-plugin',
      resolveId(id) {
        if (id.endsWith('.data.js')) {
          return `\0${id}`
        }
      },
      async load(id) {
        if (id.startsWith('\0') && id.endsWith('.data.js')) {
          const dataLoader = await import(id.slice(1))
          const data = await dataLoader.default.load()
          return `export default ${JSON.stringify(data)}`
        }
      },
    },
  ],
})
```

```vue
<script setup>
import IconAccessibility from '~icons/carbon/accessibility'
import IconAccountBox from '~icons/mdi/account-box'
</script>

<template>
  <IconAccessibility />
  <IconAccountBox style="font-size: 2em; color: red" />
</template>
```





```ts
import { defineConfig } from 'vite'
import { loadIcon } from 'iconify'

export default defineConfig({
  plugins: [
    {
      name: 'icons',
      resolveId(id) {
        if (id.startsWith('~icons/')) {
          return '\0' + id
        }
      },
      async load(id) {
        if (id.startsWith('\0~icons/')) {
          const iconName = id.slice(7)
          const svg = await loadIcon(iconName)
          return `export default ${JSON.stringify(svg)}`
        }
      },
    },
  ],
})
```

```
1  import { sha } from '~build/info'
2  import now from '~build/time'
3
4  console.log(`Build ${sha} at ${now}`)
```

Build 9c9e79dc3fd1f38df0a3e5756e2ef0eedac2b310 at Tue May 19 2026 19:21:17 GMT+0200 (Central European Summer Time)

```ts
import { execSync } from 'child_process'
import { defineConfig } from 'vite'

export default defineConfig({
  plugins: [
    {
      name: 'build-info',
      resolveId(id) {
        if (id === '~build/time' || id === '~build/git') {
          return '\0' + id
        }
      },
      load(id) {
        if (id === '\0~build/time') {
          return `export default ${JSON.stringify(new Date().toISOString())}`
        }
        if (id === '\0~build/git') {
          const sha = execSync('git rev-parse HEAD').toString().trim()
          return `export default ${JSON.stringify(sha)}`
        }
      },
    },
  ],
})
```

Virtualization - Info Plugin - Virtual Information

Virtualization in 3 Points



1. **Vite can respond to requests with virtual modules**
   Modules that do not exist on the disk but are generated on the fly by a plugin

2. **To create a virtual module, use the resolveId and load hooks**
   Take the ownership of an import with resolveId and return the code with load

3. **Used in many plugins and very powerful**
   It allows you to inject dynamic data, generate code on the fly, and much more




```
export default function myVirtualModulePlugin() {
  const virtualModuleId = 'virtual:my-module'
  const resolvedVirtualModuleId = `\0${virtualModuleId}`

  return {
    name: 'my-virtual-module-plugin',
    resolveId(id) {
      if (id === virtualModuleId) {
        return resolvedVirtualModuleId
      }
    },
    load(id) {
      if (id === resolvedVirtualModuleId) {
        // Do whatever you want
      }
    },
  }
}
```

Hot Module Replacement (HMR)

Update modules in the browser without a full page reload, preserving application state.

Middleware

Add additional routes to the Vite dev server to handle custom API requests or serve dynamic content.

Command Runner

Execute custom commands alongside the Vite dev server, with access to the Vite configuration and lifecycle.

Inter-process Communication

Allow different processes to communicate with each other to share data.

Macros

Transform source code at build time to enable new syntax or features that are not natively supported by JavaScript.

Server Framework

Extend Vite's dev server capabilities to build custom backends, APIs, or full-stack applications.

Hot Module Replacement (HMR)

6 / 17 · 35%

6 VOTES

Middleware - A Virtual File

5 / 17 · 29%

5 VOTES

Run Plugin - A Plugin for Running Commands

0 / 17 · 0%

0 VOTES

Laravel Vite - Inter-process Communication

2 / 17 · 12%

2 VOTES

unplugin-macro - A Plugin for Creating Macros


0 / 17 · 0%

0 VOTES

Nitro - A Backend

4 / 17 · 24%

4 VOTES


Elements
Console
Sources
Network
Performance
Memory
Application
Security
All
Fetch/XHR
Doc
CSS
JS
Font
Img
Media
Manifest
Socket
Wasm
Other
Name
Method
Status
Protocol
Type
Initiator
Size
Time
Waterfall
1 localhost GET 200 http/1.1 document Other 0.7 kB 6 ms
2 JS @vite/client GET 200 http/1.1 script (index):4 185 kB 14 ms
3 JS main.ts GET 200 http/1.1 script (index):13 0.5 kB 11 ms
5 JS App.vue GET 200 http/1.1 script main.ts:3 3.2 kB 13 ms
4 vite-hmr GET 101 websocket websocket @vite/client:744 0.0 kB 0 ms
5 JS App.vue?t=17729... GET 200 http/1.1 script @vite/client:821 3.2 kB 13 ms

```
export default function myHmrPlugin() {
  return {
    name: 'my-hmr-plugin',
    handleHotUpdate(ctx) {
      const { file, server, modules } = ctx
      if (file.endsWith('.myext')) {
        const mod = server.moduleGraph.getModuleById(file)
        if (mod) {
          server.moduleGraph.invalidateModule(mod)
        }
      }
    },
  }
}
```

```
import sirv from 'sirv'


{
  name: 'vite-plugin-inspect',
  configureServer(server) {
    server.middlewares.use(`${base}/__inspect`, sirv(DIR_CLIENT, {
      single: true,
      dev: true,
    }))
  }
}
```

```
import { defineConfig } from 'vite'
import { run } from 'vite-plugin-run'

export default defineConfig({
  plugins: [
    run([
      {
        name: 'generate ziggy types',
        run: ['php', 'artisan', 'ziggy:generate', '--types'],
        pattern: [/web.php$/, /api.php$/],
      }
    ]),
  ],
})
```

```
import { execSync } from 'node:child_process'
import { defineConfig } from 'vite'

export default defineConfig({
  plugins: [
    {
      name: 'vite-plugin-run',
      handleHotUpdate({ file }) {
        if (/web\.php$/.test(file)) {
          execSync('php artisan ziggy:generate --types')
        }
      }
    }
  ]
})
```



Ask Page →

← Send Page

Server logo

Ask Assets →

← Send Assets

Server logo

```
import fs from 'node:fs'

export default function laravel() {
  return {
    name: 'vite-plugin-laravel',
    configureServer(server) {
      server.httpServer?.once('listening', () => {
        const address = server.httpServer?.address()
        if (isAddressInfo(address)) {
          const viteDevServerUrl = resolveDevServerUrl(address, server.config)

          fs.writeFileSync('./public/hot', `${viteDevServerUrl}${server.config.base.replace(/\/$/, '')}`)
        }
      })
    }
  }
}
```

```ts
export function getRandom() {
  return Math.random()
}
export const buildTime = Date.now()
```

```ts
import { buildTime, getRandom } from './macros' with { type: 'macro' }

getRandom()
buildTime
```


```ts
import { defineConfig } from 'vite'

export default defineConfig({
  plugins: [
    {
      name: 'macro',
      async transform(code, id) {
        if (id.endsWith('.ts')) {
          const program = babelParse(code)
          const macros = collectMacro(program)

          for (macro of macros) {
            const result = await executeMacro(macro)
            code = replaceMacroWithResult(code, macro, result)
          }

          return code
        }
      }
    }
  ]
})
```

Nitro as a Backend


Ask Page →
← Forward Response
Server logo
Forward Request →
← Send Response
Server logo

```ts
export default defineConfig({
  plugins: [(() => {
    return {
      name: 'nitro',
      configureServer(server) {
        server.middlewares.use((req, res, next) => {
          if (isNitroRequest(req.url)) {
            nitroDevMiddleware(req, res, next)
          }
          else {
            next()
          }
        })
      }
    }
  })()]
})
```

It was always the same pipeline

Browser side

Request

```
import './style.css'
```

Request

```
import 'virtual:my-module'
```

Event

```
file change / HTTP request
```

SAME ENGINE

Vite pipeline

`resolveId`
Intercept, redirect, virtualize

aliases
virtual modules
auto-routes

`load`
Read, fetch, or generate code

filesystem
API data
build info

`transform`
Transform any code on the fly

CSS
Vue / JSX
Markdown / macros

Plugins

CSS, JSX, Vue, images, Markdown...

Generated modules

Routes, icons, virtual data, build information...

Around the pipeline

HMR, middleware, commands, backend, lifecycle hooks...

What to Keep in Mind



1. **A pipeline between your files and the browser**
   Each request goes through Vite, which can transform modules on demand

2. **Plugins can create modules that do not exist**
   Virtual modules, routes, icons, build info... everything can be generated on demand

3. **Everything can be extended by a plugin**
   Code transformation, HMR, middlewares, side effects, macros, backend...




```ts
export default defineConfig({
  plugins: [
    (() => {
      return {
        name: 'my-awesome-plugin',
        resolveId(id) {}, // if you want to create virtual modules
        load(id) {}, // if you want to create virtual modules
        transform(code, id) {}, // if you want to transform modules
        handleHotUpdate(ctx) {}, // if you want to handle HMR
        configureServer(server) {}, // if you want to do something to the dev server
        // ... and many more hooks for different capabilities
      }
    })()
  ]
})
```




```ts
import { defineConfig } from 'vite'

export default defineConfig({
  plugins: [
    {
      name: 'vue-plugin',
      transform: {
        filter: /\.vue$/,
        handler(code, id) {}
      }
    },
  ]
})
```

In 45 minutes, you discovered what you need to build your Vite plugin.





C'était

Au cœur d'une pipeline : démystifions Vite et ses plugins

Pour **MiXiT** (16 avril 2026)

Présenté par  Estéban Soubiran

⬇️ Votre feedback ⬇️

example.com